

Weight

16 lbs

Model

CC900F

## CC900F TYPE 12 COMPACT CABINET COOLER AIR-TO-AIR FLUSH-MOUNT MODEL

Rating @ 20°C \( \Delta T\) BTU / hr

4.500


Amps Current Draw at 115 volts AC


0.6


Fan [ <u>Size</u> 2 x 6"

Dimensions-Inches (H x W x D) 15 x 13-7/8 x 7-7/8

Efficiency: 66.0 Watts / °C  $\Delta T$  based on average internal cabinet temperature.










## Outside View





## **SPECIFICATIONS**

- 1. UL Listed for TYPE 12 environments.
- 2. CC900F Rated cooling: 1,320 Watts at 20°C ∆T (66.0W/°C, mounted to an uninsulated 72" X 36" X 24" Cabinet)
- 3. Designed for surface mounting on outside of cabinet.
- 4. Housing is aluminum (color is black). Stainless steel is available.
- 5. Equipped with mounting gasket to maintain air tight seal.
- 6. Internal 6-ft. power cord with 3-prong plug is standard for AC powered units.
- 7. Available with VAC (115 & 230) and VDC (12, 24, & 48) fans. DC powered units include junction box, consult website.
- 8. Unit may be mounted vertically (as shown) or horizontally.
- 9. Optional: inlet air-filter kit available upon request.
- 10. For design, quote, and sizing assistance: call (866) 936-6736.







1010 O'Brien Drive

**CC900F TYPE 12** 

CCS-PBD-7.2.2-883352-B