

AIR-TO-AIR DROP-IN MODEL



| Standard Models | Weight (lbs) | Efficiency (Watts/°C) | Performance (BTU/hr) | Amps/ Fan @ 115V | Fan dimensions | Height | Width | Depth |
|-----------------|--------------|-----------------------|----------------------|------------------|----------------|--------|-------|-------|
| CC200 | 6 | 16.5 | 1,100 | 0.4 | 2-4" | 11 1/2 | 5 1/8 | 4 5/8 |
| CC800 | 16 | 55.2 | 3,800 | 0.6 | 2-6" | 15 | 7 3/4 | 7 |
| CC2000 | 28 | 10.4 | 7,500 | 1.2 | 4-6" | 30 | 7 3/4 | 7 |

The above units require a 2-3 week delivery time. Additional units available: CC100, CC500, CC1200 and CC1400 require a delivery time of 5 to 6 weeks.

AIR-TO-AIR FLUSH MOUNT MODEL



| Standard Models | Weight (lbs) | Efficiency (Watts/°C) | Performance (BTU/hr) | Amps/ Fan @ 115V | Fan dimensions | Height | Width | Depth |
|-----------------|--------------|-----------------------|----------------------|------------------|----------------|--------|--------|-------|
| CC400F | 10 | 20.4 | 1,400 | 0.4 | 2-4" | 22 1/2 | 6 1/4 | 4 |
| CC600F | 14 | 49.2 | 3,300 | 0.6 | 2-6" | 30 | 8 3/4 | 4 |
| CC900F | 16 | 66.0 | 4,500 | 0.6 | 2-6" | 15 | 13 7/8 | 7 7/8 |
| CC2500F | 30 | 104 | 7,100 | 1.2 | 4-6" | 29 | 13 7/8 | 7 7/8 |

The above units require a 2-3 week delivery time. Additional units available: CC254, CC1300 and CC4000 require a delivery time of 5 to 6 weeks.

AIR-TO-WATER FLUSH MOUNT MODEL



| Standard Models | Wight (lbs) | Efficiency (Watts/°C) | Performance (BTU/hr) | Amps/ Fan @ 115V | Fan dimensions | Height | Width | Depth |
|-----------------|-------------|-----------------------|----------------------|------------------|----------------|--------|--------|-------|
| CC02060 | 9 | 24.5 | 3,350 | 0.2 | 1-4" | 22 1/2 | 6 1/4 | 4 |
| CC3060 | 13 | 68.8 | 9,300 | 0.3 | 1-6" | 30 | 8 3/4 | 4 |
| CC6360/61 | 32 | 159.7 | 21,800 | 0.9 | 3-6" | 29 | 13 7/8 | 8 |

The above units require a 2-3 week delivery time. Additional units available: CC3260 and CC9000 require a delivery time of 5 to 6 weeks.

STAINLESS STEEL MODELS



| Standard Models | Wight (lbs) | Efficiency (Watts/°C) | Performance (BTU/hr) | Amps/ Fan @ 115V | Fan dimensions | Height | Width | Depth |
|-----------------|-------------|-----------------------|----------------------|------------------|----------------|--------|--------|---------|
| CC405/07 | 15 | 20.4 | 1,400 | 0.5 | 2-4" | 22 | 6 1/4 | 4 1/16 |
| CC605/07 | 23 | 49.4 | 3,300 | 0.72 | 2-6" | 30 | 8 3/4 | 4 1/16 |
| CC905/07 | 30 | 66.0 | 4,500 | 0.72 | 2-6" | 16 3/8 | 13 7/8 | 7 15/16 |
| CC1305/07 | 40 | 75.0 | 5,100 | 0.72 | 2-6" | 23 3/8 | 13 7/8 | 7 15/16 |
| CC2505/07 | 48 | 104.0 | 7,100 | 1.44 | 4-6" | 30 3/8 | 13 7/8 | 7 15/16 |

The above units require a 2-3 week delivery time. Additional units available: CC254 and CC4000 require a delivery time of 5 to 6 weeks.

STAINLESS STEEL MODELS



| Standard Models | Wight (lbs) | Efficiency (Watts/°C) | Performance (BTU/hr) | Amps/ Fan @ 115V | Fan dimensions | Height | Width | Depth |
|-----------------|-------------|-----------------------|----------------------|------------------|----------------|--------|--------|-------|
| CC401F | 15 | 20.4 | 1,400 | 0.4 | 2-4" | 22 1/2 | 6 1/4 | 4 |
| CC601F | 23 | 49.4 | 3,300 | 0.6 | 2-6" | 30 | 8 3/4 | 4 |
| CC901F | 30 | 66.0 | 4,500 | 0.6 | 2-6" | 15 | 13 7/8 | 7 7/8 |
| CC1301F | 40 | 75.0 | 5,100 | 0.6 | 2-6" | 22 | 13 7/8 | 7 7/8 |
| CC2501F | 48 | 104.0 | 7,100 | 1.2 | 4-6" | 29 | 13 7/8 | 7 7/8 |

UL/cUL, Type 4X, Class 1/Div 2, Group A, B, C and D, ATEX/IECEX, Class I/Zone 2, IP66 Air-Air and Air-Water Heat Exchanger Models available.

DISPOSABLE AND ALUMINUM (REUSABLE) FILTER KITS AVAILABLE

*Typical rated performance mounted in a 72" x 36" x 24" uninsulated metal enclosure at 20°C AT room temperature.

** Same but at 40°C AT the cooling water temperature